

MODELO			LGH-50RX5-E				LGH-65RX5-E				LGH-80RX5-E			
Alimentación Eléctrica			50Hz / Monofásica 220-240V				50Hz / Monofásica 220-240V				50Hz / Monofásica 220-240V			
Velocidad			Extra High	High	Low	Extra Low	Extra High	High	Low	Extra Low	Extra High	High	Low	Extra Low
Características eléctricas	Corriente	A	1.2-1.25	1.0-1.0	0.85-0.85	0.4-0.4	1.7-1.8	1.5-1.5	1.2-1.2	0.6-0.6	1.75-1.75	1.6-1.6	1.45-1.45	0.60-0.65
	Consumo	W	255-286	207-228	175-190	80-95	350-380	308-322	248-265	120-140	380-415	345-370	315-340	125-145
Volumen de aire	m ³ /h		500	500	390	180	650	650	520	265	800	800	700	355
	l/s		139	139	108	50	181	181	144	74	222	222	194	99
Presión estática externa	mm.c.a.		15.3-15.8	6.6-9.2	4.1-6.1	1.0	11.2-12.2	6.1-8.2	4.1-5.1	0.8	14.8-15.3	10.7-12.2	8.2-9.7	2
	Pa		150-155	65-90	40-60	10	110-120	60-80	40-50	8	145-150	105-120	80-95	20
Rendimiento sensible			(%)	78.0	78.0	81.0	86.0	77.0	77.0	80.0	86.0	79.0	79.0	80.5
Rendimiento entálpico	Calefacción	(%)	69.0	69.0	71.0	78.0	68.5	68.5	70.5	78.0	71.0	71.0	72.5	79.5
	Refrigeración	(%)	66.5	66.5	68.0	77.0	66.0	66.0	68.5	77.0	70.0	70.0	71.5	79.5
Nivel sonoro ⁽¹⁾			dB	33-34	30.5-32	26.5-28	19	34-34.5	32-33	28.5-31.5	22	33.5-34.5	32-33	30-31
Dimensions	Ancho	mm	888				908				1144			
	Fondo	mm	1016				954				1004			
	Alto	mm	315				386				399			
Peso			Kg				40				53			
Corriente de arranque máxima			A				Menor a 3,0				Menor a 4,4			

MODELO			LGH-100RX5-E				LGH-150RX5-E			LGH-200RX5-E		
Alimentación Eléctrica			50Hz / Monofásica 220-240V				50Hz / Monofásica 220-240V			50Hz / Monofásica 220-240V		
Velocidad			Extra High	High	Low	Extra Low	Extra High	High	Low	Extra High	High	Low
Características eléctricas	Corriente	A	2.3-2.4	2.1-2.1	1.7-1.7	0.9-0.9	3.5-3.5	3.2-3.2	2.9-2.9	4.8-4.8	4.2-4.2	3.4-3.4
	Consumo	W	500-535	445-475	350-380	175-200	760-830	690-740	630-680	1035-1100	910-980	715-785
Volumen de aire	m ³ /h		1000	1000	755	415	1500	1500	1300	2000	2000	1580
	l/s		278	278	210	115	417	417	361	556	556	439
Presión estática externa	mm.c.a.		16.3-17.3	10.2-11.2	5.6-6.1	1.8	16.3-17.8	13.3-13.8	9.7-10.2	16.3-16.8	10.2-10.7	6.1-6.6
	Pa		160-170	100-110	55-60	18	160-175	130-135	95-100	160-165	100-105	60-65
Rendimiento sensible			(%)	80.0	80.0	83.0	87.0	80.0	80.0	81.0	80.0	80.0
Rendimiento entálpico	Calefacción	(%)	72.5	72.5	74.0	80.0	72.0	72.0	72.5	72.5	72.5	73.5
	Refrigeración	(%)	71.0	71.0	73.0	79.0	70.5	70.5	71.5	71.0	71.0	72.0
Nivel sonoro ⁽¹⁾			dB	36-37	34-35	31-32.5	21-22	38-39	36-37.5	33.5-35	39.5-40	37-38
Dimensions	Ancho	mm	1144				1144			1144		
	Fondo	mm	1231				1004			1231		
	Alto	mm	399				798			798		
Peso			Kg				105			118		
Corriente de arranque máxima			A				Menor a 4,6			Menor a 7,3		

Notas: (1) Nivel sonoro medido a 1,5 m bajo el equipo en una cámara anecoica.